


JCM 201 Steel Couplings 14" and Larger



201 STEEL COUPLINGS 14" AND LARGER

NOM. PIPE SIZE (IN.)	PIPE O.D. RANGE (IN.)	SLEEVE LENGTH & THICKNESS	NO. OF BOLTS	CATALOG NUMBER	PRICE EACH	(E) EPOXY COAT ADD TO LIST	(SS) STAINLESS STEEL 304 HARDWARE ADD TO LIST	APPR. WT. EA. (LBS.)
14	15.30	3/8 X 7	8	201-153007	\$ 536.40	\$ 25.00	\$ 212.80	85
14	15.65	3/8 X 7	8	201-156507	544.30	25.00	212.80	85
14	16.75	3/8 X 7	10	201-167507	581.50	25.00	266.00	89
16	17.40	3/8 X 7	10	201-174007	583.20	25.00	266.00	90
16	17.80	3/8 X 7	10	201-178007	590.30	25.00	266.00	90
16	18.88	3/8 X 7	10	201-188807	619.40	25.00	266.00	95
18	19.50	3/8 X 7	12	201-195007	622.50	25.00	319.20	113
18	19.92	3/8 X 7	12	201-199207	634.50	25.00	319.20	115
20	21.60	3/8 X 7	12	201-216007	856.30	P.O.A.	P.O.A.	126
20	22.06	3/8 X 7	14	201-220607	864.80	P.O.A.	P.O.A.	126
24	25.80	3/8 X 7	15	201-258007	973.10	P.O.A.	P.O.A.	141
24	26.32	3/8 X 7	15	201-263207	991.60	P.O.A.	P.O.A.	147
30	31.74	3/8 X 7	16	201-317407	P.O.A.	P.O.A.	P.O.A.	200
30	32.00	1/2 X 10	16	201-320009	P.O.A.	P.O.A.	P.O.A.	210
36	37.96	1/2 X 10	18	201-379609	P.O.A.	P.O.A.	P.O.A.	273
36	38.30	1/2 X 10	18	201-383009	P.O.A.	P.O.A.	P.O.A.	278
42	44.20	1/2 X 10	20	201-442009	P.O.A.	P.O.A.	P.O.A.	338
42	44.50	1/2 X 10	20	201-445009	P.O.A.	P.O.A.	P.O.A.	338
48	50.50	1/2 X 10	22	201-505009	P.O.A.	P.O.A.	P.O.A.	375
48	50.80	1/2 X 10	22	201-508009	P.O.A.	P.O.A.	P.O.A.	375

Other Sizes Available Upon Request

*For Sizes 2" through 16" See JCM 210 Ductile Iron Couplings

Note: Applications in which pipe may move out of the coupling, proper anchorage of the pipe must be provided.

Material Specifications:

Sizes 1/2" through 2":

MIDDLE RING: ASTM A-36

FOLLOWERS: Ductile Iron ASTM A-536

BOLTS: ASTM A242 low alloy with yellow dichromate seal. Optional Stainless Steel bolts available.

Sizes 2-1/2" through 12":

MIDDLE RING: ASTM A-36

FOLLOWERS: Ductile Iron ASTM A-536

BOLTS: Corrosion resistant, high strength low alloy (AWWA C-111, ANSI A21.11). Optional Stainless Steel bolts available.

Sizes 14" and Larger:

MIDDLE RING: ASTM A-36

FOLLOWERS: ASTM A-36

BOLTS: Corrosion resistant, high strength low alloy (AWWA C-111, ANSI A21.11). Optional Stainless Steel bolts available.

Gaskets: Specially compounded new rubber polymer for superior shelf life and resistance to permanent set. Recommended for water, salt solutions, mild acids, bases and natural gas.

Finish: Heavy coat of corrosion resistant shop coat primer. Optional Fusion Epoxy Coating available (AWWA C-213).