


JCM 230 and 231 HDPE Pipe Stiffeners



New, Advanced Design Provides...

- Corrosion Resistance
- Rigid Reinforcement of Pipe Wall for Pipe Connections
- Accurate Pipe I.D. Sizing maintains proper Outside Diameter
- 1/8" Tapered Insert End provides for Easy Installation
- 90° 1/8" Flared End Secures Stiffener to End of Pipe
- Positive Reinforcement without interference

JCM HDPE Pipe Stiffeners are designed to support the interior wall of HDPE for critical pipe joining applications. Recommended for all pipe end connections utilizing mechanical bolt-on fittings, the JCM Pipe Stiffeners support the pipe's end and controls the "necking down" reaction to the pressure applied during normal installation of fittings used in pipe joining applications.

The JCM HDPE Pipe Stiffeners are formed of stainless steel, 304 or 316 material, to the **actual inside pipe diameter provided by the customer**. This accurate formation provides for ease of installation and maintains the proper outside diameter for a successful, trouble free application that provides long-term service.

JCM Pipe Stiffeners are available for Steel Size and Ductile Iron Size HDPE in SDR11, 13.5, 17, 21, 26, 32.5

JCM Pipe Stiffeners Material Specifications: ASTM - 240 - TP 304 Stainless Steel or 316 Stainless Steel

Nominal Pipe Size	230 Stiffener 6" Width	Price Each	231 Stiffener 12" Width	Price Each
4	230-04-xxxx	\$ 48.90	231-04-xxxx	\$ 97.50
6	230-06-xxxx	52.70	231-06-xxxx	105.20
8	230-08-xxxx	57.30	231-08-xxxx	114.60
10	230-10-xxxx	62.20	231-10-xxxx	124.40
12	230-12-xxxx	67.70	231-12-xxxx	135.50
14	230-14-xxxx	70.00	231-14-xxxx	139.90
16	230-16-xxxx	77.40	231-16-xxxx	154.80
18	230-18-xxxx	81.60	231-18-xxxx	163.10
20	230-20-xxxx	86.60	231-20-xxxx	173.50
22	230-22-xxxx	99.20	231-22-xxxx	198.10
24	230-24-xxxx	123.90	231-24-xxxx	247.80
30	230-30-xxxx	148.60	231-30-xxxx	297.40
36	230-36-xxxx	198.10	231-36-xxxx	396.20

Smallest I.D./O.D. available 3.65 - Sizes larger than 36" available upon request

Stiffeners provided as 304 Stainless Steel. Optional 316 Stainless Steel available - priced on application.

Nominal Size Stiffeners 4" - 22" are 17 Gauge Stainless Steel Material

Nominal Size Stiffeners 24" - 36" are 12 Gauge Stainless Steel Material

HOW TO ORDER

1. Select nominal pipe size of HDPE.
 2. Select Width of Stiffener (Model 230 - 6" wide or Model 231 - 12" wide).
 3. Insert **actual HDPE pipe I.D. (provided by customer) @ xxxx**. The pipe I.D. determines the stiffener O.D. and completes the order number.
- Example:** To order a 304 stainless, 12" wide stiffener, for steel size 8" nominal SDR 17 pipe, with an actual pipe I.D. of 7.55, order number: 231-08-0755.

Note: JCM recommends fusion joints as a primary method of connection. Mechanical fittings are a secondary and limiting choice. JCM 230 Pipe Stiffeners are designed for use with mechanical couplings, clamps and fittings where stiffening of the pipe is necessary for proper gasket seal. Caution needs to be taken to prevent (1) shear loading on the joint, (2) migration of the stiffener out of the end of the pipe from lack of a back load on stiffener rim or load on the stiffener. Applications in which pipe may move out of the fitting, correct anchorage of the pipe must be provided.

Price Book Effective May 6, 2005. Cancels all previous prices. Prices subject to change without notice.