


JCM 303 Fabricated Flanged Coupling Adapters



The JCM 303 Fabricated Flanged Coupling Adapter provides a simple means of joining plain end pipe to flanged fittings, valves and equipment. Fabricated from steel, these fittings are readily available in large or small sizes with a standard AWWA Class D flange. Special or heavier flanges are available on request.

How To Order

1. Determine pipe O.D. and flange size & type to be joined.
2. Order catalog Number indicating O.D. and flange size selected.

EXAMPLE: For 17.40 O.D. ductile iron pipe to be joined to 16" Class D flange, order: 303-1740 x16

JCM 303 FLANGED COUPLING ADAPTERS

| NOM. PIPE SIZE (IN.) | PIPE O.D. RANGE (IN.) | NOMINAL FLANGE SIZE | CATALOG NUMBER | PRICE EACH | APPR. WT. EACH (LBS.) |
|----------------------|-----------------------|---------------------|----------------|------------|-----------------------|
| 3 | 3.50 | 3 | 303-0350 X 3 | \$ 283.10 | 19 |
| 4 | 4.50 | 4 | 303-0450 X 4 | 305.30 | 25 |
| 4 | 4.80 - 5.00 | 4 | 303-0480 X 4 | 345.40 | 26 |
| 5 | 5.56 | 5 | 303-0556 X 5 | 380.50 | 32 |
| 6 | 6.63 | 6 | 303-0663 X 6 | 431.70 | 38 |
| 6 | 6.90 - 7.10 | 6 | 303-0690 X 6 | 445.70 | 40 |
| 8 | 8.63 | 8 | 303-0863 X 8 | 536.10 | 50 |
| 8 | 9.05 - 9.30 | 8 | 303-0905 X 8 | 552.10 | 52 |
| 10 | 10.75 | 10 | 303-1075 X 10 | 672.70 | 58 |
| 10 | 11.10 - 11.40 | 10 | 303-1110 X 10 | 688.70 | 61 |
| 12 | 12.75 | 12 | 303-1275 X 12 | 800.50 | 78 |
| 12 | 13.20 - 13.50 | 12 | 303-1320 X 12 | 813.10 | 84 |
| 14 | 14.00 | 14 | 303-1400 X 14 | 925.70 | 90 |
| 14 | 15.30 | 14 | 303-1530 X 14 | 961.70 | 110 |
| 14 | 15.65 | 14 | 303-1565 X 14 | 982.40 | 110 |
| 16 | 16.00 | 16 | 303-1600 X 16 | 1,036.00 | 113 |
| 16 | 17.40 | 16 | 303-1740 X 16 | 1,164.40 | 130 |
| 16 | 17.80 | 16 | 303-1780 X 16 | 1,194.60 | 137 |
| 18 | 18.00 | 18 | 303-1800 X 18 | 1,230.70 | 137 |
| 18 | 19.50 | 18 | 303-1950 X 18 | 1,399.40 | 144 |
| 18 | 19.92 | 18 | 303-1992 X 18 | 1,443.50 | 144 |
| 20 | 20.00 | 20 | 303-2000 X 20 | 1,473.80 | 158 |
| 20 | 21.60 | 20 | 303-2160 X 20 | 1,680.50 | 162 |
| 20 | 22.06 | 20 | 303-2206 X 20 | 1,710.70 | 162 |
| 24 | 24.00 | 24 | 303-2400 X 24 | 1,811.00 | 192 |
| 24 | 25.80 | 24 | 303-2580 X 24 | 1,938.30 | 220 |
| 24 | 26.32 | 24 | 303-2632 X 24 | 2,037.80 | 220 |
| 30 | 32.00 | 30 | 303-3200 X 30 | P.O.A. | 442 |
| 36 | 38.30 | 36 | 303-3830 X 36 | P.O.A. | 602 |
| 42 | 44.50 | 42 | 303-4450 X 42 | P.O.A. | 771 |
| 48 | 50.80 | 48 | 303-5080 X 48 | P.O.A. | 885 |

Other sizes available upon request.

Epoxy coating and stainless steel bolts are available as an extra.

NOTE: Applications in which pipe may move out of the coupling, correct anchorage of the pipe must be provided.